

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	3501	((re\$1initializ\$6 refresh\$3) with object\$1)	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:22
L2	4608	719/310,313-316,318,320, 328-330.ccls.	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:21
L3	92	1 and 2	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:21
L4	1	1 and (referenc\$3 near3 (application\$1 program\$1) near5 (hold adj2 (state\$1 status)))	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:23
L5	1639	((re\$1initializ\$6 refresh\$3) near5 object\$1)	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:22
L6	65	2 and 5	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:22
L7	1766	717/108-116.ccls.	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:23
L8	30	5 and 7	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:23
L9	1	7 and (referenc\$3 near3 (application\$1 program\$1) near5 (hold adj2 (state\$1 status)))	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:24

L10	1	7 and (referenc\$3 near3 (application\$1 program\$1) near5 (hold near3 (state\$1 status)))	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:24
L11	1604	((hold\$3 stop\$4) near3 (state status)) near5 (object\$1 component\$1)	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:25
L12	26	5 and 11	US-PGPUB; USPAT; EPO; DERWENT; IBM_TDB	OR	OFF	2006/01/11 13:25

[Sign in](#)

[Web](#)
[Images](#)
[Groups](#)
[News](#)
[Froogle](#)
[Local](#)
[New!](#)
[more »](#)

[Advanced Search](#)  
[Preferences](#)

**Web**Results 1 - 10 of about 45,200 for **reinitialize object reference application hold state**. (0.27 seconds)**Java Best Practices Collection 2001 by Ahmet Haliloglu**

The **application** developer must explicitly determine the **state** attributes and store ... This implies that **objects** should not **hold references** to instances of ...

[www.geocities.com/javabestpractices/servlet.html](http://www.geocities.com/javabestpractices/servlet.html) - 15k - [Cached](#) - [Similar pages](#)

**Java Servlets: Design Issues**

This implies that **objects** should not **hold references** to instances of servlets ... **Objects** implementing **application** logic can not maintain **state** unless these ...

[www.subrahmanyam.com/articles/servlets/ServletIssues.html](http://www.subrahmanyam.com/articles/servlets/ServletIssues.html) - 23k - [Cached](#) - [Similar pages](#)

**State Bundles for Persistence**

Do you, Programmer, take this **Object** to be part of the persistent **state** of your **application**, to have and to **hold**, through maintenance and iterations, ...

[www.erights.org/e/StateSerialization.html](http://www.erights.org/e/StateSerialization.html) - 46k - [Cached](#) - [Similar pages](#)

**C#: A Message Queuing Service Application (.NET Development ...**

**Application** error handling within the .NET Framework is based around an ... Once an **object reference** is obtained it is cast into the appropriate interface: ...

[msdn.microsoft.com/library/en-us/dndotnet/html/csharpmsmq.asp](http://msdn.microsoft.com/library/en-us/dndotnet/html/csharpmsmq.asp) - 73k - Jan 9, 2006 - [Cached](#) - [Similar pages](#)

**Papers - COOTS '96**

The fields of a class **hold** the **state** of the class. Each field is strongly typed as either a **reference** to an **object** or to one of the built-in primitives ...

[www.usenix.org/publications/library/proceedings/coots96/full\\_papers/riggs/](http://www.usenix.org/publications/library/proceedings/coots96/full_papers/riggs/) - [Similar pages](#)

**Java Performance Tuning: Chapter 4: Object Creation**

When the **reference object** is cleared, it is added to the ReferenceQueue instance and can then be processed by the **application**, eg, explicitly deleted from a ...

[www.oreilly.com/catalog/javapt/chapter/ch04.html](http://www.oreilly.com/catalog/javapt/chapter/ch04.html) - 84k - [Cached](#) - [Similar pages](#)

**Implementing Cloning**

For example, before the **Application** passes an **object** to a property page, ... In many cases, a referenced **object** may **hold references** to yet more **objects**, ...

[edndoc.esri.com/arcobjects/9.0/ExtendingArcObjects/Ch02/Cloning.htm](http://edndoc.esri.com/arcobjects/9.0/ExtendingArcObjects/Ch02/Cloning.htm) - 30k - [Cached](#) - [Similar pages](#)

**Clustering Objects**

A process-level **object reference** (ID) type is defined and used to ... Persistent media merely **hold** snapshots of **state** information needed to **reinitialize** or ...

[g.oswego.edu/dl/oosd/ch23.html](http://g.oswego.edu/dl/oosd/ch23.html) - 62k - [Cached](#) - [Similar pages](#)

**[PDF] Using Khazana to Support Distributed Application Development 1 ...**

File Format: PDF/Adobe Acrobat - [View as HTML](#)

share **state** between **applications** or reuse code devel- ... First, we converted all **object references** in shared data. structures into Khazana smart pointers, ...

[www.cs.utah.edu/techreports/1999/pdf/UUCS-99-008.pdf](http://www.cs.utah.edu/techreports/1999/pdf/UUCS-99-008.pdf) - [Similar pages](#)

**INTRODUCTION**

This implies that **objects** should not hold **references** to instances of servlets,  
... **State** management, by storing pre-identified **state** of the **application** ...

[www.bridgeport.edu/sed/projects/cs597/Spring\\_2003/mbompaly/design.html](http://www.bridgeport.edu/sed/projects/cs597/Spring_2003/mbompaly/design.html) - 66k - [Cached](#) - [Similar pages](#)

Try your search again on [Google Book Search](#)

Google

Result Page:    [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#)    [Next](#)



Google Desktop Search



Free! Instantly find your email, files, media and web history. [Download now.](#)

reinitialize object reference applicati

Search

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2006 Google

[Sign in](#)
[Web](#)
[Images](#)
[Groups](#)
[News](#)
[Froogle](#)
[Local](#)
[New!](#)
[more »](#)

reinitialize refresh object reference application

Search

[Advanced Search](#)  
[Preferences](#)
**Web**Results 1 - 10 of about 13,700 for **reinitialize refresh object reference application hold state**. (0.22 seconds)**Cisco IOS IP Application Services Command Reference, Release 12.4T ...**

Book-level PDF: Cisco IOS IP Application Services Command Reference, Release 12.4T

... If an **object** is not tracked, its **state** changes do not affect the Hot ...

www.cisco.com/en/US/products/ps6441/products\_command\_reference\_chapter09186a00804a88d2.html - 139k -

[Cached](#) - [Similar pages](#)[\[PDF\] standby authentication](#)File Format: PDF/Adobe Acrobat - [View as HTML](#)

Cisco IOS IP Application Services Command Reference. standby mac-refresh ...

priority on the basis of the **state** of the **object**, use the standby track command ...www.cisco.com/univercd/cc/td/doc/product/software/ios124/124tcr/tiap\_r/apl\_s2ht.pdf - [Similar pages](#)**Implementing Entity Beans (Java Enterprise in a Nutshell)**Later, you can read the **object** back from its serialized **state** and obtain a**reference** to the remote bean **object**, using the getEJBObject() method on the ...www.unix.org.ua/orelly/java-ent/jenut/ch07\_06.htm - 63k - [Cached](#) - [Similar pages](#)[\[PDF\] The Intel 376 Family for Embedded Processor Applications](#)

File Format: PDF/Adobe Acrobat

Th is the **hold state**, the **state** entered in response to a ... disables the wait-**state**generator. DRAM **refresh** controller. The 82370 DRAM ...doi.ieeeecomputersociety.org/10.1109/40.537 - [Similar pages](#)**Controlling Page Sequencing with an Event-Driven State Machine ...**However, Web **applications** use URLs both to retrieve **objects** and to initiate ...in the Session scope used to **hold** the **state** machine's internal variables. ...coldfusion.sys-con.com/read/46786.htm - 96k - [Cached](#) - [Similar pages](#)**Sample Chapter from 101 Microsoft® Visual Basic® .NET Applications ...**When a thread is terminated or goes into a sleep **state**, it's placed into the ...The sample **application** demonstrates how to use all three **objects** on the ...www.microsoft.com/mspress/books/sampchap/6510.asp - 90k - [Cached](#) - [Similar pages](#)**Performance Tuning ASP Pages and SQL Server Databases**If a COM **object** is cached in an **Application object**, all calls to the **object** haveto be ... Instead of using session variables to store **state** information, ...www.sql-server-performance.com/asp\_sql\_server.asp - 83k - Jan 10, 2006 - [Cached](#) - [Similar pages](#)**R****reference** data. In SOM, **application**-specific data that a server uses to identifyor describe an **object** in DSOM. The data, represented by a sequence of up to ...www.unet.univie.ac.at/aix/aixuser/glossary/R.htm - 56k - [Cached](#) - [Similar pages](#)[\[PDF\] Production Debugging for .NET Framework Applications](#)File Format: PDF/Adobe Acrobat - [View as HTML](#)For each **application**, the GC maintains a tree of **references** that tracks the ...Click **Allocate 20 MB Objects** again instead of clicking **Refresh Stats**. The ...